



Providing Effective Solutions for Audio Visual Systems

Audio Balun

Features:

- Allows audio signal to be transmitted via Cat 5 Cable
- High Reliability and Durability
- Housed in a fire retardant wall mountable Case
- Low cost, high quality and performance
- Passive device (no power supply required)
- Stable over working temperature between 0 °C to +55 °C

Application:

The Audio Balun enables structured audio distribution of dual mono or single stereo audio signals via Cat 5/Cat 6 UTP cable.

This Balun provides a low cost and versatile cabling solution for any audio distribution.

Specifications:

Bandwidth:	10Hz to 50KHz +/- 3dB
Impedance:	RCA 600 Ω (Red/White-Audio) to RJ45 100 Ω
Connector:	RCA x 2 (Right/Red - Left/White)
Maximum distance:	Up to 1000 metres
Isolation:	500V
Nominal Level:	1.0 volt
Insertion Loss:	1dB
Common Mode Rejection:	Greater than 40dB
Cable UTP:	24 AWG or lower solid copper twisted pair wires
Impedance:	100 ohm at 1MHz
Max. Capacitance :	20 pf/ft
Attenuation:	6.6dB/100ft at 1MHz
RJ45 Pin out:	Left: 3 & 6 Right: 1 & 2
Temperature:	Operating: 0 to 55° C Storage: -20 to 85° C Humidity: up to 95%
Dimensions:	49.2 x 43.0 x 21.5mm

Note: Specifications subject to change without notice.



Audio Balun
2 RCA Female to 1 RJ45
Part Number: E10670



Wired Limited

Unit B, 2 Centennial Highway, Ngauranga, Wellington
Phone: 04 499 4110 Fax: 04 499 4114 Mobile 027 294 7332
Email: sales@wirednz.co.nz

www.wirednz.co.nz