



Product Bulletin

TC-FD1012T/R SERIES DIGITALLY ENCODED VIDEO WITH RETURN DATA



DESCRIPTION

The Tiandy TC-FD1012T/R Series video and data transmitter and receiver support broadcast quality transmission of 8-bit digitally encoded video and return data over one multimode and singlemode optical fiber. The modules are compatible with NTSC, PAL and SECAM CCTV camera systems and support RS-485 data protocol. Plug and Play design ensures the convenience of installation and operation. User adjustments are never required. The modules come in either standalone or rack mount versions.

SPECIFICATIONS

VIDEO

Video Input:	1 volt pk-pk (75 ohms)
Bandwidth:	5 Hz - 8 MHz
Bit Resolution:	8-bit
Differential Gain:	< 2%
Differential Phase:	< 0.6°
Tilt:	< 1%
S/N Ratio:	67dB (Weighed)

DATA

Data Interface:	RS-485
Data Rate:	100Kbps
Bit Error Rate:	10 ⁻⁹

WAVELENGTH

1310/1550nm, Singlemode
850/1310nm, Multimode

OPTICAL EMITTER

Laser Diode

FEATURES

- 8-Bit Uncompressed Video Transmission
- NTSC, PAL or SECAM Video Standards
- Transmit up to 30km without Optical Attenuation
- Simultaneous Transmission of Video and Data
- WDM Technology for Higher Reliability
- No EMI, RFI, Cross Talk and Ground Loop
- No Electrical or Optical Adjustments Required
- LED Indicators Instantly Monitoring System Performance
- Standalone or Rack Mount

NUMBER OF FIBERS

1

CONNECTORS

Optical:	FC (SC & ST Optional)
Video:	BNC
Data:	Terminal Blocks with Screw Clamps

GENERAL

Power Supply:	DC5V @ 300mA
Size:	120mm x 116mm x 30mm
MTBF:	> 100,000 hours
Operating Temp:	-30°C to +50°C
Storage Temp:	-40°C to +85°C
Relative Humidity:	0% to 95% (no condensing)

Wired Limited

Unit B, 2 Centennial Highway, Ngauranga, Wellington
 Phone: 04 499 4110 Fax: 04 499 4114 Mobile 027 294 7332
 Email: sales@wirednz.co.nz

www.wirednz.co.nz